



CRISP

SPECIFICATIONS / TECHNICAL DATA

KEY FEATURES

- 1,250W High Volume Snow Machine
- Lower Operating noise for Noise-sensitive Environments
- Auto-Clean Process
- Compact Light Weight Robust Design
- Onboard LCD Touch Control Panel
- Optional MaagFLY Wireless DMX Transceiver
- Optional MagRF
- Optional MagRemotes (VIDI)



PRODUCT DESCRIPTION

CRISP™ is a high volume compact lightweight snow machine with advanced technology providing adjustable snowflake size, along with a lower operating noise for noise-sensitive environments. The new the Auto-Clean feature, provides less clogging and requires less maintenance. Features include an easy-to-use onboard LCD touch screen control panel, intuitive DMX-512, and RDM control, durable aluminum housing, and optional wired and wireless remote control options.

PRODUCT SPECIFICATIONS

DYNAMIC EFFECTS

- Snow Adjustment: 0-100%
- Fan Speed Adjustment 50% or 100%
- Self-Clean Function

CONTROL

- .2 Card Inputs (For optional Magfly, & MagRF cards)
- RDM (Remote Device Management)
- Control Protocol: DMX512.DMX Modes: 3 (1 / 3 / 5)
- On-Board Timing Control
- 5 Factory Presets
- 4-pin Wired Remote Input
- Touch Screen Display
- MagRemote VIDI

CONNECTIONS

- Data Connectors: 5-pin locking XLR In/Out
- 4-pin Connector for optional wired remote
- Locking Power Connector

COMPATIBLE FLUID

Recommended fluid: Atmosity Premium Snow Fluid. APS-1LC (Concentrate = 20L) , APS-4LC (Conentrate = 80L), APS-10LC (Concentrate = 200L) APS-4L, APS-20L

MAGMATIC



CRISP

SPECIFICATIONS / TECHNICAL DATA

CONSTRUCTION / PHYSICAL / PERFORMANCE

Dimensions (LxWxH): 20.81in x 15.94in x 15.95in / (518 w/Antenna) x 415 x 405mm

Weight: 33.5 lbs / 15.2kg

External Visual Fluid Level Detection

Fluid Tank Capacity: 5L.

Fluid Consumption: 16.9oz/min / 500ml/min

ELECTRICAL

Power Consumption: 1250w

Input Voltage: U.S. Version - 120VAC @ 60Hz and Europe Version - 230 - 240VAC @ 50Hz

Breaker Size: 15A (120V version). Breaker Size: 9A (230-240V version)

CERTIFICATIONS / QUALIFICATIONS / THERMAL

IP Rating: IP20, dry location

Maximum Temperature (Ambient): 104° F (40° C)

Exterior Surface Temperature: 122° F (50° C)

WHAT'S INCLUDED

Hanging Bracket

14 AWG Locking Power Cable

OPTIONAL ACCESSORIES

MagFLY Card

MagRF Card

RATINGS / APPROVALS

CE | cETLus | FCC | IP20

Specifications and documentation subject to change without notice.

