





150W RGBMA IP65 LED PAR

**DATA SHEET** 



## **KEY FEATURES**

150W RGBMA LED Engine

5,474 Total Fixture Lumen Output (Sphere)

Field Replaceable Lenses

Stand-Alone Control with Touch Encoder and OLED Display

Smooth 16-bit Selectable Dimming Modes and Curves

RDM (Remote Device Management)

NFC & Aria x2 Wireless Device Management

6.25" Gel Frame and Four Lenses (10°, 22°, 30°, 55°)

Included

IP65 Rated

Compact, powerful, and versatile, the **KL PAR IP COMPACT** delivers exceptional lighting performance in a small, rugged package. Designed for any environment, this IP65-rated LED fixture offers precise color temperature control, full-spectrum rendering, and consistent wash coverage, powered by a highly efficient RGBMA engine that provides up to 5,474 lumens.

Its advanced control software delivers exceptional color accuracy (CRI 94.9, TLCI 95), 16-bit variable CCT control, and adjustable LED refresh frequency, making it perfect for film, television, and live events. With multiple lens options, DMX/RDM compatibility, and a touch bar encoder for instant adjustments, it's ready for any production need.

Streamline your lighting setup and discover how the **KL PAR IP COMPACT** can elevate your next production.









#### 150W RGBMA IP65 LED PAR

## **SPECIFICATIONS**

#### **SOURCE**

150W 6000K RGBMA LED Engine 30,000 Hour Average LED Life\*

\*Test lab conditions. May vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

### PHOTOMETRIC DATA

Total Lumen Output: 5,474 (Integrating Sphere) 4,722 (Goniometer) CRI 94.9 TLCI 95

### **INCLUDED LENSES**

VNSP (10°) NSP (22°) MFL (30°) WFL (55°)

#### **EFFECTS**

Variable Strobe Rate: 1- 20Hz Dim-to-Warm/ Red Shift Emulation Variable 16-bit Dimming Modes and Curves

### **COLOR**

RGBMA Color Array CMY Emulation 16bit Fully Variable CCT 2400K - 8500K Green/Magenta Shift Virtual Gel Swatch Book

#### **CONTROL / CONNECTIONS**

8 DMX Channel Modes (1, 4, 6, 10, 11, 19, 9, 15)
Manual and DMX Controlled Dimmer and Color
Single Touch Bar Encoder
4 Button Control Panel, LED Display
RDM (Remote Device Management)
Aria x2 Wireless Device Management
NFC Configuration
IP65 5pin DMX and IP65 Locking Power Cable In/
Out

## SIZE / WEIGHT

Length: 7.2" (183mm)

Length (Yoke 0°): 14.25" (362mm)

Width: 10.1" (257mm)

Height (Fixture Body): 7.2" (183mm) Height (Yoke 90°): 14.2" (361mm)

Weight: 12.1 lbs (5.5kg)

## **ELECTRICAL / THERMAL**

AC 100-240V - 50/60Hz 200W Max Power Consumption Power Thru Capacity: 10A (6 units @115V, 12 units @240V) 5°F to 113°F (-15°C to 45°C) BTU/hr (+/- 10%) 682

## **INCLUDED ITEMS**

Gel Frame Safety Cable 4 Lenses (10°, 22°, 30°, 55°) IP65 Locking Power Cable

#### **OPTIONAL ITEMS**

6.25" Barndoors
Omega Bracket
4 Wire Hardwire Installation Plate (HWP404)
2 Wire Hardwire Installation Plate (HWP202)

#### **APPROVALS / RATINGS**

CE | cETLus | IP65 | FCC | UKCA












150W RGBMA IP65 LED PAR

**DIMENSIONS** 



# **ORDERING INFORMATION**

KLP250	1236100197	KL Par IP Compact
HWP404	1236300104	4 Wire Hardware Installation Plate
HWP202	PENDING	2 Wire Hardware Installation Plate
PENDING	PENDING	6.25" Barndoor



