



EPT6IP™

SKU# EPT600

The EPT6IP™ is a new 6mm pixel pitch modular outdoor rated Pro Touring LED display. It's light weight durable die-cast aluminum frame and (4) piece modular design, allows for easy installation and service. The EPT6IP™ uses the latest dot correction technology which provides full color uniformity and brightness. The EPT6IP™ is ideal for outdoor Pro Touring portable installations.

SPECIFICATIONS

Pixel Pitch: 6.67mm
Physical Density: 22,500(dots/m2)
LED Configuration: 1R1G1B
LED Type: SMD Chip
Module Size: 320x320mm
Module resolution: 48x48
Drive Model: MBI5151
Scanning Mode: 1/6
Horizontal and Vertical View angle: 120°
Brightness: 5000cd/m2
Gray Scale: 14bit
Refresh rate: 1920Hz
Cabinet Resolution: 96x96
Cabinet Max Power Consumption: 252W
Cabinet Average Power Consumption: 101W
Cabinet Size: 640x640mm
Cabinet Weight: 38.6 lbs. (17.5kg)
Cabinet Material: Aluminum
Input Voltage: AC110V220V +/-10%, 50/60Hz
Life Span: 100,000 Hour
Protection Level: IP65
Calibration Module



IP65



Intertek
4010765

