



# VOLKS | LICHT

# VOLKS|LICHT

---



“Now the well known GLP quality  
is even more affordable”

---

#### Power supply

Power consumption 180 VA (Watt)  
Power Input ~100 - 240V AC, 50-60 Hz (wide range input)  
Fuse protection Micro fuse 5x20mm, T 4A

#### Operational Parameters

Max. Ambient 45°C (integrated overheating switch)  
Temperature  
Mounting position fully operational whether it hangs or is mounted to the wall. It can also be operated while standing on the floor.

#### Lighting System - Additive Color mixing

LED Type 60x Luxeon Rebel High - Power - LEDs  
Lifetime 50.000h

#### RGB Model

21 Green LEDs, 21 blue LEDs, 18 Red LEDs, wavelength optimized for a maximum presentable color space

#### White Model

42 cold white LEDs, 18 warm white LEDs allow a continuously adjustable color temperature

#### Optical System

Exchangeable optical carrier with 11° light distribution angle (24° optional)

#### Shutter / Dimmer

Strobe - Effect with variable speed between 1 - 10 flashes per second, Random - Strobe, Pulse Effects  
Continuous Dimmer 0 - 100%

#### DMX Control

Standard USITT DMX-512, 3 pole XLR;  
[+] = Pin 3 [-] = Pin 2 [Ground] = Pin 1.  
DMX- Addressing starts at the DMX channel [001].

#### Weights and Measures

(WxLxH) 270 x 285 x 355mm  
Weight: ~ 8 kg