



PROTEUS™





PROTEUS



PROTEUS[™]
LUCIUS



PROTEUS[™]
MAXIMUS



PROTEUS[™]
EXCALIBUR

Proteus is the market's leading line of IP65-rated outdoor luminaire with weatherproof coverings, the award-winning Proteus line of moving lights. The most robust, powerful and comprehensive toolset for live events.



FULL FEATURED PERFORMANCE

Proteus Lucius and Proteus Maximus are feature-packed, all-purpose power luminaires with all-weather IP65 housings that have flexible use as a profile, spot or wash light. Ideal fixtures for any outdoor or indoor application requiring radically bright output from industry-leading hotspot LED engines, powerful looks, and stunningly precise gobos and colors, they provide designers the power to cover huge areas and long distances with remarkable precision. As elegant as they are powerful, they provide the designer a complete FX package to highlight any stage and performer.



MULTI-FUNCTION

Engineered to empower designer creativity, the 3-in-1 Proteus Hybrid is arguably the most successful IP65-rated moving head on the market. With full CMY color mixing plus CTO and loaded with professional design features, this high-performance lighting solution is designed to excel under any weather condition, generating outstanding beams and aerial effects in the largest applications.



CUT THROUGH

The industries brightest, Proteus Hybrid is ideally suited for all types of live events and spectacles. Full color mixing and prism control and a variety of gobo sets set this unit apart, and its ability to divide the air with powerful shafts of color.



PROTEUS



PROTEUS
HYBRID



PROTEUSSM
SMARTY HYBRID



PROTEUSSM
RAYZOR 760

minaires. By eliminating the need for costly and cumbersome
g heads offers designers, integrators or any lighting professional
lighting in virtually any weather or adverse environment.

THE SKY

Best beam fixture is
outdoor nighttime
color mixing, beam
and an array of gobos
allowing designers
with incredibly
color and light.



BE SMART

The Proteus Smarty Hybrid is a multi-functional hybrid beam, spot, wash luminaire using the 6,000-hour Flex 200 discharge lamp. Impressively powerful for such a compact fixture and capable of zooming in all modes, its full CMY color mixing system plus CTO, extra colors, gobos and prisms make it a valuable all-in-one design tool for any show.



WASH, BEAM, SPARKLE

The ultimate LED wash / beam with an extremely wide zoom range and pixel control for powerful eye candy effects, the Proteus Rayzor 760's unique SparkLED™ background illumination system gives it an extra layer of effect that stands out on any show. Continuous 360° pan/tilt rotation and a compact, lightweight design make it the most versatile and effective IP65 wash fixture to perform in any size application.



www.ElationProfessional.com

Product Overview



PROTEUS LUCIUS	PROTEUS MAXIMUS	PROTEUS EXCALIBUR
SOURCE <ul style="list-style-type: none"> 580W 6,500K bright white Hotspot LED engine 30,000 hour average LED life* 	SOURCE <ul style="list-style-type: none"> 950W 6,500K bright white Hotspot LED engine 30,000 hour Average LED life* 	SOURCE <ul style="list-style-type: none"> 550W 6,500K Philips FLEX 4000h Entertainment Cycle Lamp Life
PHOTOMETRIC DATA <ul style="list-style-type: none"> 31,000 total lumen output CRI 71+ (85+ with HCRI filter) 	PHOTOMETRIC DATA <ul style="list-style-type: none"> 50,000 total lumen output CRI 70+ (82+ HCRI filter) 	PHOTOMETRIC DATA <ul style="list-style-type: none"> 20,000 Total Lumen Output CRI 75+
EFFECTS <ul style="list-style-type: none"> 5.5 - 55° motorized zoom 4 rotating full blackout framing, +/-50° index animation wheel 4-facet and linear rotating prisms Light and Wash frost filters iris High speed electronic strobe 	EFFECTS <ul style="list-style-type: none"> 5.5 - 55° motorized zoom (Large 180mm front aperture) 4 rotating full blackout framing, +/-50° index Animation wheel 4-facet and linear rotating prisms Light and Wash frost filters iris High speed electronic strobe 	EFFECTS <ul style="list-style-type: none"> 1.7° Beam Angle, Variable Focus 3.1° Beam Expander 8-Facet , 4 Facet Linear Prism 2 Light and Wash Frost filters
COLOR <ul style="list-style-type: none"> Full CMY+ CTO color mixing 5 dichroic colors including high CRI filter 	COLOR <ul style="list-style-type: none"> Full CMY + CTO color mixing 6 Dichroic colors including high CRI filter and UV 	COLOR <ul style="list-style-type: none"> CMY Mix 14 Dichroic Colors including CTO and UV
GOBOS <ul style="list-style-type: none"> 3 gobo wheels 13 rotating/indexing interchangeable glass gobos 7 static glass gobos 	GOBOS <ul style="list-style-type: none"> 2 gobo wheels 6 rotating / indexing Interchangeable glass gobos 7 static glass gobos 	GOBOS <ul style="list-style-type: none"> 2 Gobo Wheels 8 Rotating / Indexing Interchangeable glassGobos 17 Position Static Gobo Wheel
CONTROL / CONNECTIONS <ul style="list-style-type: none"> 2 DMX modes DMX, RDM, Art-NET, sACN Locking IP65 5pin XLR + Ethernet in/out Locking IP65 power in 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 2 DMX modes (37 / 61) DMX, RDM, Art-NET, sACN Locking IP65 5pin XLR + Ethernet in/out Locking IP65 power in 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 2 DMX Channel Modes DMX, RDM, Art-NET, sACN Locking IP65 5pin DMX + Ethernet in/out Locking IP65 power in
SIZE (LxWxH)/ WEIGHT <ul style="list-style-type: none"> 17.5 x 19.6 x 28.1 in 445 x 499 x 715 mm Weight: 91.4 lbs. (41.5kg) 	SIZE (LxWxH)/ WEIGHT <ul style="list-style-type: none"> 18 x 23.3 x 32.5 in 458 x 591 x 825 mm Weight: 117 lbs. (53kg) 	SIZE (LxWxH)/ WEIGHT <ul style="list-style-type: none"> 19.4 x 19.98 x 27.49 in 493 x 507.4 x 698 mm Weight: 101.4lbs (46kg)
PROTEUS HYBRID	PROTEUS SMARTY HYBRID	PROTEUS RAYZOR 760
SOURCE <ul style="list-style-type: none"> Philips MSD 21R 470W 8,000K lamp 1,000 hour average lamp life* 	SOURCE <ul style="list-style-type: none"> Philips™ MSD platinum 200 Flex 280W lamp Up To 6,000 hour lamp life* 	SOURCE <ul style="list-style-type: none"> (7) 60W Osram RGBW LEDs (28) 2W white SparkLED™ 50,000 hour average LED life*
PHOTOMETRIC DATA (15m) <ul style="list-style-type: none"> 80CRI >23,000 lumens 	PHOTOMETRIC DATA (preliminary) <ul style="list-style-type: none"> Up to 11,000 total lumen output 	PHOTOMETRIC DATA <ul style="list-style-type: none"> Up to 8000 total lumen output
EFFECTS <ul style="list-style-type: none"> Motorized zoom, 2° beam to 38° spot or 40° wash animation wheel Frost filter hybrid wash effect High speed strobe 	EFFECTS <ul style="list-style-type: none"> Beam, spot, wash modes Motorized zoom 1°-18° beam, 3°-27° Spot, 5°-33° wash Wash frost filter 16-facet and 5-facet linear prisms High speed strobe 	EFFECTS <ul style="list-style-type: none"> 5° - 77° beam to wash zoom angle Linear color temperature presets (2700-8000K) RGBW color mixing and pixel control White SparkLED™ lens effect High speed electronic strobe
COLOR <ul style="list-style-type: none"> Full CMY + CTO color mixing 14 dichroic colors including CTB, CTO, and UV 	COLOR <ul style="list-style-type: none"> Full CMY color mixing 13 colors including quad color, CTO, CTB, and UV 	COLOR <ul style="list-style-type: none"> (7) RGBW LEDs (28) white SparkLED™
GOBOS <ul style="list-style-type: none"> 8 interchangeable rotating / indexing glass gobos 14 static-stamped Metal Gobos 	GOBOS <ul style="list-style-type: none"> 2 gobo wheels 8 rotating / indexing Interchangeable glass gobos 12 static-stamped metal gobos 	GOBOS <ul style="list-style-type: none"> N/A
CONTROL / CONNECTIONS <ul style="list-style-type: none"> 3 DMX modes(24/26/37) DMX, RDM, Art-NET, sACN Elation's E-FLY™ wireless Locking IP65 5pin XLR + Ethernet in/out Locking IP65 power in 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 2 DMX modes (20 / 34) DMX, RDM, Art-NET, sACN Locking IP65 5pin XLR +Ethernet in/out Locking IP65 power in 	CONTROL / CONNECTIONS <ul style="list-style-type: none"> 3 DMX channel modes DMX, RDM, Art-NET, sACN Locking IP65 5pin XLR I+ Ethernet in/out Locking IP65 power in
SIZE (LxWxH) / WEIGHT <ul style="list-style-type: none"> 17.5 x 22.5 x 31.5 in 445 x 572 x 800 mm Weight: 84.0 lbs. (38 kg) 	SIZE (LxWxH) / WEIGHT <ul style="list-style-type: none"> 17.5 x 17.88 x 26.97 in 444.71 x 459 x 685 mm Weight: 78.26 lbs. (35.5kg) 	SIZE (LxWxH) / WEIGHT <ul style="list-style-type: none"> 14.5 x 11.6 x 17.4 in 367 x 295 x 442 mm Weight: 13kg (28.6 lbs.)

CREATE THE VISION | DELIVER THE EXPERIENCE



Scan or
Click me to
learn more.

Elation Professional
United States | México | The Netherlands
www.elationlighting.com • Toll Free: (866) 245-6726
Copyright © 2022 Elation Lighting Inc. All rights reserved.



PROTEUS

*Lamp/ LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming, Gobos & Colors. Specifications subject to change without notice